

# ECOftech Taurus 155E

## Datasheet



### Parameters

### ECOftech Taurus 155E

<b>Printhead</b>	1440 nozzles • Variable dots • 7 • 14 • 21 picoliters	
<b>Number of printheads</b>	1	
<b>Resolution</b>	Up to 1440 dpi	
<b>Ink</b>	<b>Type</b>	Eco-Solvent
	<b>Color</b>	4 colors (CMYK)
	<b>Capacity</b>	1 liter per color
<b>Media</b>	<b>Max. printing width</b>	59.84" (1,520 mm)
	<b>Max. media width</b>	61" (1,550 mm)
	<b>Feeding System</b>	Roll or sheet
	<b>Automatic Take Up System</b>	Included
	<b>Types</b>	Banner, mesh, vinyl, perforated vinyl, canvas, textile, polyester fabric
<b>Print Mode</b>	<b>Production 4 Pass</b>	162 sq.ft./h (15 m <sup>2</sup> /h)
	<b>Quality 6 Pass</b>	129 sq.ft./h (12 m <sup>2</sup> /h)
	<b>H. Quality 8 Pass</b>	86 sq.ft./h (8 m <sup>2</sup> /h)
<b>Cleaning System</b>	Auto cleaning	
<b>Heating and Cooling System</b>	Preheater, front heater and cooling fans	
<b>Interface</b>	Network interface RJ45	
<b>Rip Software</b>	Flexi Print 12 / Maintop	
<b>Voltage</b>	AC 220V, 50Hz / 60Hz	
<b>Power Consumption</b>	Heater: 800W (7A) Printer: 200W (1.5A)	
<b>Operational Temperature</b>	68° - 77° F (20° - 25° C) Humidity 40 - 60%, non-condensing	
<b>Printer Dimensions (Length x Width x Height)</b>	92" x 30" x 50" (2,337 x 762 x 1,270 mm)	
<b>Package Dimensions (Length x Width x Height)</b>	100" x 27" x 28" ( 2,540 x 686 x 712 mm)	
<b>Printer weight</b>	327 lbs (149 kg)	
<b>Package weight</b>	450 lbs (204 kg)	