

# One Sign Perforated Vinyl GO1020

Datasheet

## Specifications

## One Sign Perforated Vinyl GO1020

<b>PVC Type:</b>	Calendered monomeric soft PVC film
<b>PVC Thickness:</b>	±10 microns
<b>PVC Color:</b>	White with black reverse side
<b>PVC Shrinkage:</b>	≅ 0.8%
<b>PVC Surface Tension:</b>	≅ 30dn/cm
<b>PVC Opacity:</b>	>99%
<b>PVC Holes No.</b>	Average 130/sq in
<b>PVC Hole Diameter:</b>	1.6mm
<b>PVC Distance Between Holes:</b>	2.4mm
<b>PVC Hole Coverage:</b>	41%
<b>Adhesive Type:</b>	Clear solvent based removable pressure sensitive glue
<b>Adhesive Weight:</b>	30 ± 2 g/m <sup>2</sup>
<b>Adhesion Temperature:</b>	from 15°C ~ 40°C (59°F ~ 104°F)
<b>Adhesive Peeling Force:</b>	≅ 5N/25mm
<b>Adhesive Holding Power:</b>	≅ 800min
<b>Liner Type:</b>	Laminated Kraft Paper with dual layers for greater ink absorption and faster drying
<b>Liner Color:</b>	White
<b>Liner Weight:</b>	140g
<b>Liner Release Force:</b>	0.4~1N/4cm
<b>Removable Durability:</b>	One year cleanly removable glue on clean glass surface at temperature of 23~25°C (73°F ~ 77°F) and relative humidity of 50~60%
<b>Packaging:</b>	Carton box
<b>Storage time:</b>	12 months under ordinary conditions at temperature of 22°C (72°F) and relative humidity of 50-55%
<b>Sizes:</b>	54" x 164' (1.37m x 50m) 54" x 100' (1.37m x 30.4m)
<b>Applications:</b>	One way vision media is utilized in digital UV, solvent, eco-solvent and Silk Screen printing for signage displays, vehicle and subway graphics, window and glass wall decoration.

All the above information is true based on laboratory analysis. Nonetheless, the manufacturer is not liable to any claims or compensation due to this data.